

# Timer report

**Command:** status

**Subcommand:** timer

**Supported Platforms:** Native,UFT,Selenium,Appium

**Supported OS:** Android, iOS

Adds a timer report to the test. The measured timer result is reported from the test into the generated Single Test Report.

## Description

Adds the timer report retrieved via the *Get timer* command into the test's Single Test Report named by the *name* parameter, and with the timing measurement indicated by the *result* parameter..

## Parameters

</span>

\* Mandatory parameter

## Request & Response

### Request

```
https://mycloud.perfectomobile.com/services/executions/john@perfectomobile.com_controller_16-11-08_09_26_26_940?operation=command&securityToken=<your_token>&command=status&subcommand=timer&param.name=none&param.result=5000
```

### JSON Response

```
{
  "executionId": "john@perfectomobile.com_controller_16-11-08_09_26_26_940",
  "reason": "Success",
  "returnValue": "SUCCESS",
  "testGridReportUrl": "https://mycloud.reporting-stg.perfectomobile.com?externalId[0]=john@perfectomobile.com_controller_16-11-08_09_26_26_940",
  "singleTestReportUrl": "https://mycloud.perfectomobile.com/nexperience/singletest/report/?reportRepositoryKey=PRIVATE:controller/161108/controller_16-11-08_09_26_26_940.xml&ownerId=john@perfectomobile.com&sharingCode=166ca97d-a844-443e-bb78-99da59f69f8f",
  "description": "Success",
  "reportKey": "PRIVATE:controller/161108/controller_16-11-08_09_26_26_940.xml",
  "completed": "true",
  "flowEndCode": "SUCCEEDED"
}
```